

## Weathered Membrane Cleaner Product Data

### Weathered Membrane Cleaner

Weathered Membrane Cleaner is used to clean both new and old EPDM membrane. It helps to loosen and remove dirt and other contaminants from the surface of the membranes and leaves a suitable surface for the subsequent application of primer. Weathered Membrane Cleaner should be used when preparing an adhesive splice.

### Intended Uses

Weathered Membrane Cleaner is used to clean both new and in-service EPDM membrane.

### Features and Benefits

- Easily removes dirt and other contaminants from EPDM membranes
- Prepares EPDM membrane for application of primer, adhesives and tape
- Prepares aged or contaminated TPO membrane for seaming



### Application\*

1. Remove as much loose material as possible from the membrane surface where the adhesive or pressure sensitive product will be applied by sweeping or wiping the area with a dry rag. Extreme conditions of accumulated dirt may require detergent and water cleaning (rinse area thoroughly with CLEAN water and allow to dry).
2. Saturate a clean HP Splice Wipe (or equivalent) with Weathered Membrane Cleaner. SCRUB the area in a circular motion. Continue to clean the area, changing wipes frequently, until the surface is a consistent matte black colour with no streaking. Additional cleaning is required at factory seams (scrub parallel to the seam). Allow to dry.
3. Apply primer according to product instructions and/or roofing system specification.

\* REVIEW CURRENT SPECIFICATIONS AND DETAILS FOR SPECIFIC APPLICATION REQUIREMENTS.



# Weathered Membrane Cleaner Product Data

## Precautions

1. WARNING! HARMFUL IF SWALLOWED. FLAMMABLE LIQUID. MAY BE IRRITATING TO SKIN AND EYES.

2. Wash thoroughly after handling. Avoid contact with eyes, skin and clothing. Use of solvent resistant gloves and safety glasses recommended. Keep away from heat, sparks, motors and open flame. DO NOT SMOKE WHILE USING. Keep lid closed when not in use. Keep out of reach of children.

3. If swallowed, DO NOT INDUCE VOMITING. Call physician immediately. In case of eye contact, flush with water for at least 15 minutes. In case of skin contact, wash with soap and water. If irritation develops, call physician. Avoid breathing vapours. Keep container closed when not in use. Use with adequate ventilation. If inhaled, remove to fresh air. If not breathing, perform artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately. During application, efforts must be made to prevent fumes from entering the building via air ventilation ducts. Do not place open containers or mix adhesive near fresh air intake units. When possible, shut down or seal off the closest units.

4. In case of fire handle as a solvent or gasoline fire. Use dry chemical, carbon dioxide or foam fire extinguishers. Water fog or spray may be used to smother the fire and cool containers. Do not use a solid stream of water to fight fire because it can scatter and spread the fire.

## Coverage Rates

1. Coverage rate depends on the age of the membrane and the amount of dirt/debris on the surface. Assume 121 m<sup>2</sup> (one surface) per gallon.

ClassicBond Weathered Membrane Cleaner	
Typical Properties & Characteristics*	
Colour	Clear
Solids	0%
Flash Point	18°C
Boiling Point	127°C
Packaging	18.9 Litre or 1 litre

Before using this product please ensure that you have been supplied with and have read carefully the following information:

1. The product labels
2. ClassicBond Weathered Membrane Cleaner Material Safety Data Sheet