



- 1. ClassicBond EPDM Membrane
- 2. ClassicBond Decking Adhesive (See Notes)
- 3. ClassicBond Bonding Adhesive
- 4. 150mm PS Cover Strip
- 5. Suitable thermal insulation, thickness determined by U-value
- 6. Vapour Control Layer (VCL)
- 7. Structural decking
- 8. Prefabricated metal edge trim @ 300mm max centres
- 9. Pitched roof underlay
- 10. Roof tile (by others)
- 11. Lead flashing (by others)
- 12. Sure Edge front plate
- 13. Sure Edge standard back plate
- 14. Reinforced Universal Secure Strip (RUSS)
- 15. Suitable Fastener with 50mm Seam Plate

Notes:  
 1. This detail was prepared to serve as a guideline representing typical detailing conditions and illustrate the correct application of ClassicBond products only. It may be necessary to modify this detail in whole or part in accordance with specific project conditions, design or requirements.  
 2. Acrylic Decking Adhesive is for timber substrates only, all other suitable surfaces use ClassicBond Bonding Adhesive.  
 3. Spacings for fixings may need to be reduced to 150mm centres dependant on location & climatic conditions.  
 4. Diagram 2 shows use of alternate detail using SureEdge PVC drip trim.

	Title		FLAT ROOF TO PITCH ROOF TERMINATION (MANSARD)				Drawn	Checked	Approved	Scale	Date				
	Product		CB-T-2				MFO	DW	DW	1: 4@A4	03.02.14				
							Status								
							PRODUCTION								
						A		03.02.14		PRODUCTION Issue		Drawing No:	Rev:		
						Rev		Date		Comments		CB/T/2		A	