



1. ClassicBond EPDM Membrane
2. ClassicBond Decking Adhesive
3. ClassicBond Bonding Adhesive
4. Suitable thermal insulation, thickness determined by U-value
5. Vapour Control Layer (VCL)
6. Structural decking
7. Prefabricated metal edge trim - maximum fixing spacings 300mm
8. Reinforced Universal Secure Strip (RUS)
9. Suitable Fastener with 50mm Seam Plate

Notes:

1. This detail was prepared to serve as a guideline representing typical detailing conditions and illustrate the correct application of ClassicBond products only. It may be necessary to modify this detail in whole or part in accordance with specific project conditions, design or requirements.
2. Acrylic Decking Adhesive is for timber substrates only, all other suitable surfaces use ClassicBond Bonding Adhesive.
3. Spacings for trim fixings may need to be reduced to 150mm centres dependant on location & climatic conditions.
4. The maximum inside angle change before RUS is required should be no more than 9.5°.



| | | | | | | |
|---------------------------|----------|---|---------|----------|---------|-----------|
| Title EDGE TRIM | | Drawn | Checked | Approved | Scale | Date |
| | | MFO | DW | DW | 1: 4@A4 | 29.01.14 |
| Product CB-ET-1 | | Status <div style="text-align: center;">PRODUCTION</div> | | | | |
| | | Drawing No: CB/ET/1 | | | | Rev: B |
| Rev | Date | Comments | | | | |
| A | 29.01.14 | PRODUCTION Issue | | | | |