

Section 1: Identification of the Product and Company Identification

1.1. Product Identifier

Product Name: ClassicBond Sprayable Bonding Adhesive (SPB) 22L Canister
Product Code: 523001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Suppliers: Flex-R
Sandswood House
Hillbottom Road
Sands Industrial Estate
High Wycombe
Buckinghamshire
HP12 4HJ
Tel: 01494 448792 Fax: 01494 858433 Email: enq@classicbond.co.uk

1.4. Emergency telephone number

Emergency telephone 01494 448792 (NOT 24HRS Monday-Thursday 08.30 – 17.30
Friday 08.30 – 16.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture
Classification

Physical hazards Aerosol 1 - H222, H229
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards Aquatic Chronic 2 - H411
Human Health Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. May be slightly irritating to eyes.
Physicochemical The product is extremely flammable. Aerosol containers can explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing vapour/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

For the safe disposal of the canister, please refer to the appropriate technical literature

Contains

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane, ACETONE

Supplementary precautionary statements

P264 Wash contaminated skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/ doctor if you feel unwell.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIMETHYL ETHER	30-60%
CAS number: 115-10-6	EC number: 204-065-8
	REACH registration number: 01-2119472128-37-0000

Exclusive British Isles Distributors for Carlisle-SynTec and ClassicBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: : +44 (0)1494 448792 Fax: +44 (0)1494 858433

Classification

Flam. Gas 1 - H220
Press. Gas, Liquefied - H280

**hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics,
<5% nhexane**

10-30%

CAS number: –

EC number: 921-024-6

REACH registration number: 01-
2119475514-35

Classification

Flam. Liq. 2 - H225
Skin Irrit. 2 - H315
STOT SE 3 - H336
Asp. Tox. 1 - H304
Aquatic Chronic 2 - H411

ACETONE

10-30%

CAS number: 67-64-1

EC number: 200-662-2

REACH registration number: 01-
2119471330-49

Classification

Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

TOLUENE

<1%

CAS number: 108-88-3

EC number: 203-625-9

REACH registration number: 01-
2119471310-51-0051

Classification

Flam. Liq. 2 - H225
Skin Irrit. 2 - H315
Repr. 2 - H361d
STOT SE 3 - H336
STOT RE 2 - H373
Asp. Tox. 1 - H304

METHYL ACETATE

<1%

CAS number: 79-20-9

EC number: 201-185-2

REACH registration number: 01-
2119459211-47-0012

Classification

Flam. Liq. 2 - H225

Exclusive British Isles Distributors for Carlisle-SynTec and ClassicBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe,
Buckinghamshire, HP12 4HJ. Tel: : +44 (0)1494 448792 Fax: +44 (0)1494 858433

Revision Date: 08/02/2018

Eye Irrit. 2 - H319
STOT SE 3 - H336

HEXANE-norm

<1%

CAS number: 110-54-3

EC number: 203-777-6

REACH registration number: 01-2119480412-44

Classification

Flam. Liq. 2 - H225
Skin Irrit. 2 - H315
Repr. 2 - H361f
STOT SE 3 - H336
STOT RE 2 - H373
Asp. Tox. 1 - H304
Aquatic Chronic 2 - H411

ZINC DIBENZYL DITHIOCARBAMATE

<1%

CAS number: 14726-36-4

M factor (Acute) = 1
M factor (Chronic) = 1

REACH registration number: 01-2119543708-31-0002

Classification

Aquatic Acute 1 - H400
Aquatic Chronic 1 - H410

The Full Text for all Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

Exclusive British Isles Distributors for Carlisle-SynTec and ClassicBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: : +44 (0)1494 448792 Fax: +44 (0)1494 858433

Revision Date: 08/02/2018

Inhalation	Irritation of nose, throat and airway. Coughing, chest tightness, feeling of chest pressure.
Ingestion	May cause discomfort if swallowed.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	Vapour, spray or dust may cause chronic eye irritation or eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Extremely flammable.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material.
Special protective equipment for firefighters	Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Absorb spillage with non-combustible, absorbent material. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Provide adequate ventilation. Contain
--------------------------------	--

Exclusive British Isles Distributors for Carlisle-SynTec and ClassicBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe,
Buckinghamshire, HP12 4HJ. Tel: : +44 (0)1494 448792 Fax: +44 (0)1494 858433

Revision Date: 08/02/2018

spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours and spray/mists. Avoid contact with skin and eyes. Do not use in confined spaces without adequate ventilation and/or respirator. Spraying is permitted only in closed systems, spray cabinets or spray boxes with adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C.
Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m³
Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³
Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 191 mg/m³(Sk)
Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 574 mg/m³(Sk)

METHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm 616 mg/m³
Short-term exposure limit (15-minute): WEL 250 ppm 770 mg/m³

HEXANE-norm

Exclusive British Isles Distributors for Carlisle-SynTec and ClassicBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe,
Buckinghamshire, HP12 4HJ. Tel: : +44 (0)1494 448792 Fax: +44 (0)1494 858433

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³
Short-term exposure limit (15-minute): WEL

ZINC DIBENZYLDITHIOCARBAMATE

Long-term exposure limit (8-hour TWA): 6 mg/m³

Ingredient comments WEL = Workplace Exposure Limits
Sk = Can be absorbed through the skin.

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Ingredient comments WEL = Workplace Exposure Limits
DNEL Consumer - Oral; Long term systemic effects: 699 mg/kg bw/day
Workers - Oral; Long term systemic effects: 2035 mg/kg bw/day
Consumer - Dermal; Long term systemic effects: 699 mg/kg bw/day
Workers - Dermal; Long term systemic effects: 773 mg/kg bw/day
Consumer - Inhalation; Long term systemic effects: 608 mg/m³

ACETONE (CAS: 67-64-1)

Ingredient comments WEL = Workplace Exposure Limits

METHYL ACETATE (CAS: 79-20-9)

Ingredient comments WEL = Workplace Exposure Limits

TOLUENE (CAS: 108-88-3)

DNEL Workers - Inhalation; Short term systemic effects: mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection Wear chemical splash goggles.

Hand protection It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber.

Other skin and body protection Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.

Revision Date: 08/02/2018

Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Wash hands after handling. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly ventilated spaces, a supplied-air respirator must be worn. Wear a respirator fitted with the following cartridge: Gas filter, type AX.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Various colours.
Odour	Ether
Odour threshold	Not available.
pH	Not available.
Melting point	Estimated value. -141.5°C
Initial boiling point and range	Estimated value. -24.8°C @ 1013 hPa
Flash point	Estimated value. -41°C
Evaporation rate	Not applicable.
Evaporation factor	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Estimated value. : 3.3%-26.2%
Other flammability	Not applicable.
Vapour pressure	Estimated value. 5132,9 hPa @ 25°C
Vapour density	Not applicable.
Relative density	0.80 @ 20° C
Bulk density	Not applicable.
Solubility(ies)	Estimated value. 45.6 g/l water @ 25°C
Partition coefficient	Estimated value. Pow: 0.07
Auto-ignition temperature	Estimated value. 226°C
Decomposition Temperature	Not applicable.
Viscosity	Kinematic viscosity > 20.5 mm ² /s.
Explosive properties	Not available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not applicable.
Comments	Information given is applicable to the product as supplied.

Exclusive British Isles Distributors for Carlisle-SynTec and ClassicBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: : +44 (0)1494 448792 Fax: +44 (0)1494 858433

9.2. Other information

Other information	No information required.
Refractive index	Not applicable.
Particle size	Not applicable.
Molecular weight	Not applicable.
Volatility	Not applicable.
Saturation concentration	Not applicable.
Critical temperature	Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not applicable. Not relevant.
---	-------------------------------

10.4. Conditions to avoid

Conditions to avoid	Avoid contact with water. Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Strong acids. Strong alkalis.
---------------------------	-------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Oxides of nitrogen.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation

Animal data	Irritating.
--------------------	-------------

Serious eye damage/irritation

Revision Date: 08/02/2018

Serious eye damage/irritation	Moderately irritating.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Sensitising.
<u>Carcinogenicity</u>	
Carcinogenicity	Not applicable.
Target organ for carcinogenicity	No specific target organs known.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Morphological changes that are potentially reversible but provide clear evidence of marked organ dysfunction.
<u>Aspiration hazard</u>	
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.
Inhalation	Irritating to respiratory system. May cause sensitisation by inhalation.
Ingestion	May cause stomach pain or vomiting.
Skin contact	Irritating to skin. May cause sensitisation by skin contact.
Eye contact	Irritation of eyes and mucous membranes.
Acute and chronic health hazards	May cause sensitisation by skin contact. The product contains small quantities of isocyanate. May cause respiratory allergy. May cause respiratory system irritation. May cause respiratory system irritation. Frequent inhalation of vapours may cause respiratory allergy.
Route of entry	Inhalation Skin and/or eye contact
Medical symptoms	Irritation of eyes and mucous membranes. Coughing, chest tightness, feeling of chest pressure.
Medical considerations	Chronic respiratory and obstructive airway diseases.

Toxicological information on ingredients.

DIMETHYL ETHER

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV)	164,000.0
Species	Rat
ATE inhalation (gases ppm)	164,000.0

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Toxicological effects	No information available.
<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	5,840.0
Species	Rat
Notes (oral LD₅₀)	Not known. Data lacking.
ATE oral (mg/kg)	5,840.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	2,920.0
Species	Rat
Notes (dermal LD₅₀)	Data lacking.
ATE dermal (mg/kg)	2,920.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	25.2
Species	Rat
ATE inhalation (vapours mg/l)	25.2
<u>Skin corrosion/irritation</u>	
Animal data	Data lacking.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Data lacking.
<u>Aspiration hazard</u>	
Aspiration hazard	Kinematic viscosity > 20.5 mm ² /s.
Inhalation	May cause respiratory system irritation.
Ingestion	May cause stomach pain or vomiting.
Skin contact	Irritating to skin.
Eye contact	May cause severe eye irritation.
Acute and chronic health hazards	Vapour from this product may be hazardous by inhalation.
Route of entry	Inhalation Skin absorption Ingestion. Skin and/or eye contact
Target organs	No specific target organs known.
Medical symptoms	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.
Medical considerations	No information available.

ACETONE

Acute toxicity - dermal

Acute toxicity dermal (LD ₅₀ mg/kg)	5,000.0
Species	Rabbit

HEXANE-norm

Acute toxicity - inhalation

Acute toxicity inhalation (LC ₅₀ vapours mg/l)	17.6
ATE inhalation (vapours mg/l)	17.6

SECTION 12: Ecological Information

Ecological information on ingredients.

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Ecotoxicity	Dangerous for the environment.
-------------	--------------------------------

12.1. Toxicity

Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: >500 mg/l, Daphnia magna
---	---

Ecological information on ingredients.

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Acute toxicity - fish	LC ₀ , hours: >1-<10 mg/l, Algae
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 3 mg/l, Daphnia magna
Acute toxicity - aquatic plants	LC ₀ , hours: >1-<10 mg/l, Fish

ACETONE

Toxicity	Not considered toxic to fish.
Acute toxicity - fish	LC ₅₀ , 96 hours: 5540 mg/l, Freshwater fish , 96 hours: 11000 mg/l, Marinewater fish LC ₅₀ , 96 hours: 11000 mg/l, Algae
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 8800 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: 430 mg/l, Fish
Acute toxicity - microorganisms	, 30 minutes: 1000 mg/l, Activated sludge

TOLUENE

Revision Date: 08/02/2018

Acute toxicity - fish , 48 hours: > 1-10 mg/l, Freshwater fish
Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 11.5 mg/l, Daphnia magna
Acute toxicity - aquatic plants IC₅₀, 72 hours: 100 mg/l, Fish

METHYL ACETATE

Acute toxicity - fish , 96 hours: 250-350 mg/l, Brachydanio rerio (Zebra Fish)
Acute toxicity - aquatic invertebrates EC₅₀, 24 hours: 700-1000 mg/l, Daphnia magna

HEXANE-norm

Acute toxicity - fish LC₅₀, EC₅₀, IC₅₀, : 10 mg/l, Algae
Acute toxicity - aquatic invertebrates LC₅₀, EC₅₀, IC₅₀, : 10 mg/l, Daphnia magna
Acute toxicity - aquatic plants LC₅₀, EC₅₀, IC₅₀, : 10 mg/l, Fish

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.
Stability (hydrolysis) Reacts with water.
Biological oxygen demand < 10 g O₂/g substance

Ecological information on ingredients.

ACETONE

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.
Partition coefficient Estimated value. Pow: 0.07

Ecological information on ingredients.

ACETONE

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.
BCF: 3,
Partition coefficient Pow: < -0.24

METHYL ACETATE

Partition coefficient : 0.18

TOLUENE

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.
Partition coefficient Not available.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Ecological information on ingredients.

ACETONE

Mobility The product is miscible with water and may spread in water systems.
Adsorption/desorption coefficient Water - log Koc: 1.5 @ 20°C
Henry's law constant 2929-3070 Pa m³/mol @ 25°C

TOLUENE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

METHYL ACETATE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

ACETONE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

TOLUENE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

METHYL ACETATE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Ecological information on ingredients.

ACETONE

Other adverse effects Not applicable.

TOLUENE

Other adverse effects Not known.

METHYL ACETATE

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3501
UN No. (IMDG) 3501
3501 3501
UN No. (ADN) 3501

14.2. UN proper shipping name

Proper shipping name (ADR/RID) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.(Contains Dimethyl Ether)

Proper shipping name (IMDG) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.(Contains Dimethyl Ether)

Proper shipping name (ICAO) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.(Contains Dimethyl Ether)

Proper shipping name (ADN) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.(Contains Dimethyl Ether)

14.3. Transport hazard class(es)

ADR/RID class 2.1
ADR/RID classification code 8F

Revision Date: 08/02/2018

ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1
Transport labels	2.1



14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Emergency Action Code	2YE
Hazard Identification Number (ADR/RID)	23
Tunnel restriction code	(B/D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Pollution Act 1974.
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	The spraying of flammable liquids HSG178.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by Technical

Exclusive British Isles Distributors for Carlisle-SynTec and ClassicBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe,
Buckinghamshire, HP12 4HJ. Tel: : +44 (0)1494 448792 Fax: +44 (0)1494 858433

Revision Date: 08/02/2018

Revision date	02/08/2018
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
Store Between	Store Between 5°C - 25°C
Contains SVHC	NO

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.