

Section 1: Identification of the Product and Company Identification

1.1. Product Identifier

Product Name: ClassicBond Weathered Membrane Cleaner 1L
Product Code: 304066

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaner. Product for industrial use only
Uses advised against No additional information available

1.3. Details of the supplier of the safety data sheet

Suppliers: Flex-R
Sandwood House
Hillbottom Road
Sands Industrial Estate
High Wycombe
Buckinghamshire
HP12 4HJ
Tel: 01494 448792 Fax: 01494 858433 Email: enq@ClassicBond.co.uk

1.4. Emergency telephone number

Emergency telephone 01494 448792 (NOT 24HRS Monday-Thursday 08.30 – 17.30
Friday 08.30 – 16.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225
Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336
Environmental hazards Aquatic Chronic 2 - H411
Human Health Asp. Tox. 1 H304
Physicochemical No additional information available

2.2. Label elements

Pictogram



Signal word	Danger
Hazardous ingredients	Solvent naphtha (petroleum), light aliph.
Hazard statements	H225 - Highly flammable liquid and vapour H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H336 - May cause drowsiness or dizziness H411 - Toxic to aquatic life with long lasting effects
Precautionary statements	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P310 - IF SWALLOWED: Immediately call a doctor P331 - Do NOT induce vomiting P403+P235 - Store in a well-ventilated place. Keep cool P501 - Dispose of contents/container to an authorised waste collection point

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substance

SOLVENT NAPHTHA (PETROLEUM) LIGHT ALIPH.		100 %
CAS number: 64742-89-8	EC number: 265-192-2 (EC index No.) 649-267-00-0	REACH registration number:
Classification		
Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411		

3.2. Mixtures

Not applicable

The Full Text for all Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms develop, obtain medical attention.

Revision Date: 08/02/2018

Ingestion	Do NOT induce vomiting. Rinse mouth. Give 100 - 200 ml of water to drink. Do not give an unconscious person anything to drink. Obtain immediate medical attention.
Skin contact	Immediately remove contaminated clothing or footwear. Rinse skin with plenty of water or shower. If skin irritation or rash occurs: Get medical advice/attention.
Eye contact	Rinse cautiously with water for several minutes. Ensure that folded skin of eyelids is thoroughly washed with water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause drowsiness or dizziness.
Ingestion	Ingestion may cause irritation of the gastrointestinal tract. May result in aspiration into the lungs, causing chemical pneumonia.
Skin contact	Causes skin irritation.
Eye contact	May cause slight irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. Respiratory symptoms, including pulmonary oedema, may be delayed.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Foam. Dry chemical. Carbon dioxide. Water spray.
Unsuitable extinguishing media	Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	Highly flammable liquid and vapour. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.
Explosion hazard	Containers may rupture when heated.
Hazardous decomposition products in case of fire	Fire may produce irritating, corrosive and/or toxic gases. Carbon monoxide. Carbon dioxide.

5.3. Advice for firefighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from firefighting to enter drains or water courses.
Special protective equipment for firefighters	Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures Remove all sources of ignition. Evacuate unnecessary personnel. Ensure adequate ventilation.

6.1.2. For emergency responders

Protective equipment Wear suitable protective clothing and eye or face protection.

Emergency procedures Remove all sources of ignition. Use only non-sparking tools. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Ensure adequate ventilation. Avoid inhalation of vapours. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if large amounts of the product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb with earth, sand or other non-combustible material, allow to cure, and transfer to containers for later disposal. Wash spill area with soapy water. Washings must be prevented from entering surface water drains.

6.4. Reference to other sections

Reference to other sections SECTION 8: Exposure controls/personal protection. SECTION 13: Disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately grounded. Use only explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact during pregnancy/while nursing. Provide adequate ventilation. Use only outdoors or in a well-ventilated area. Avoid inhalation of vapours. Avoid contact with skin, eyes and clothing.

Hygiene measures Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Exclusive British Isles Distributors for Carlisle-SynTec and ClassicBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe,
Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

Technical measures	Keep away from open flames, hot surfaces and sources of ignition.
Storage conditions	Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a dry place. Keep cool. Protect from freezing.
Incompatible materials	Strong acids. Strong alkalis. Strong oxidizing agents.

7.3. Specific end use(s)

Specific end use(s)	Cleaner. Product for industrial use only.
----------------------------	---

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls	Provide adequate ventilation.
Personal protective equipment	Avoid all unnecessary exposure.
Eye/face protection	Chemical goggles or face shield. Standard EN 166 - Personal eye-protection.
Hand protection	Wear chemically resistant protective gloves. Standard EN 374 - Protective gloves against chemicals. Gloves should be removed and replaced if there are any signs of degradation or breakthrough.
Other skin and body protection	Long sleeved protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Environmental exposure controls	Avoid release to the environment.
Thermal hazard protection	Wear heat-resistant gloves and clothing if the product is heated.
Other information	Do not eat, drink or smoke during use. Handle in accordance with good industrial hygiene and safety procedures.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	Colourless.
Odour	Hydrocarbon
Odour threshold	No data available
pH	No data available.

Relative evaporation rate (butylacetate=1)	1
Melting point	No data available
Freezing point	No data available
Initial boiling point and range	118 - 150 °C
Flash point	18 °C (closed cup)
Auto-ignition temperature	320 °C
Decomposition temperature	No data available
Flammability (solid, gas)	Not applicable
Vapour pressure	11.5 mm Hg
Relative vapour density at 20 °C	4 (air = 1)
Relative density	0.74 - 0.76 (Water = 1)
Solubility	Insoluble in water.
Log Pow	No data available
Log Kow	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	No data available
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Explosive limits	0.9 - 7 vol %

9.2. Other information

VOC content	100 %
--------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable under normal conditions.
-------------------	---------------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
------------------	---------------------------------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Stable under normal conditions.
---	---------------------------------

10.4. Conditions to avoid

Conditions to avoid	Heat. Sparks. Ignition sources.
----------------------------	---------------------------------

10.5. Incompatible materials

Materials to avoid Strong oxidizing agents. Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire may produce irritating, corrosive and/or toxic gases. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity Not classified
Based on available data, the classification criteria are not met

Toxicological information on ingredients.

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (64742-89-8)

LD50 oral rat > 5000 mg/kg

LD50 dermal rabbit > 2000 mg/kg

LC50 inhalation rat (mg/l) > 5610 mg/l/4h

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Not classified
Based on available data, the classification criteria are not met

Respiratory or skin sensitisation Not classified
Based on available data, the classification criteria are not met

Germ cell mutagenicity Not classified
Based on available data, the classification criteria are not met

Carcinogenicity Not classified
Based on available data, the classification criteria are not met

Reproductive toxicity Not classified
Based on available data, the classification criteria are not met

Specific target organ toxicity (single exposure) May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) Not classified
Based on available data, the classification criteria are not met

Aspiration hazard May be fatal if swallowed and enters airways.

Potential adverse human health effects and symptoms Causes skin irritation. May cause slight irritation to eyes. Vapours may cause drowsiness and dizziness. Ingestion may cause irritation of the gastrointestinal tract. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

SECTION 12: Ecological Information

Exclusive British Isles Distributors for Carlisle-SynTec and ClassicBond EPDM single ply roofing materials.

Flex-R, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

12.1. Toxicity

Ecology - water Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (64742-89-8)

EC50 3.1 mg/l (72 Hours, Growth rate, Pseudokirchnerella subcapitata)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

Weathered Membrane Cleaner

Ecology - soil Insoluble in water.

12.5. Results of PBT and vPvB assessment

Sure-Seal HP-250 Primer

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Other adverse effects Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods Dispose of this material and its container at hazardous or special waste collection point.

Waste disposal recommendations Dispose in a safe manner in accordance with local/national regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Additional information Handle empty containers with care.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR) 1263
UN-No. (IATA) 1263
UN-No. (IMDG) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT RELATED MATERIAL
Proper Shipping Name (IATA) PAINT RELATED MATERIAL
Proper Shipping Name (IMDG) PAINT RELATED MATERIAL

Transport document description (ADR) UN 1263 ADHESIVES, 3, II

14.3. Transport hazard class(es)

Class (ADR/RID) 3
Class (IATA) 3
Class (IMDG) 3
Hazard labels (ADR/RID) 3



Hazard labels (IATA) 3



Danger labels (IMDG) 3



14.4. Packing group

Packing group (ADR/RID) II
Packing group (IATA) II
Packing group (IMDG) II

14.5. Environmental hazards

Dangerous for the environment
Marine pollutant



Other information

No supplementary information available.

14.6. Special precautions for user

Special transport precautions

No special precautions required.

14.6.1. Overland transport

No additional information available

14.6.2. Transport by sea

No additional information available

14.6.3. Air transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Authorisations and/or restrictions on use (Annex XVII):

Weathered Membrane Cleaner 3.a. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F

Weathered Membrane Cleaner 3.b. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

Weathered Membrane Cleaner 3.c. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

Contains no substance on the REACH candidate list

VOC content 100%

15.1.2. National regulations

National regulations No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by	Technical
Revision date	08/02/2018
Data sources	REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
Hazard statements in full	Aquatic Chronic 2 Hazardous to the aquatic environment — Chronic Hazard, Category 2 Asp. Tox. 1 Aspiration hazard, Category 1 Flam. Liq. 1 Flammable liquids, Category 1 Flam. Liq. 2 Flammable liquids, Category 2 Skin Irrit. 2 Skin corrosion/irritation, Category 2 STOT SE 3 Specific target organ toxicity — Single exposure, Category 3, Narcosis H224 Extremely flammable liquid and vapour H225 Highly flammable liquid and vapour H304 May be fatal if swallowed and enters airways H315 Causes skin irritation H336 May cause drowsiness or dizziness H411 Toxic to aquatic life with long lasting effects

NCEC SDS EU (REACH ANNEX II)

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use