

## ClassicBond PRO MCUP Canister Flushing System

The optional Moisture-Curing Polyurethane (MCPU) Canister Flushing System aids in ensuring that ClassicBond PRO MCUP application kit remains free from blockages. Compatible with many available PU cleaning aerosols.

### Intended Uses

The ClassicBond PRO MCUP Canister Flushing System allows the contractor to reduce down-time due to blockages in the MCUP application gun and hose. The Flushing Kit allows polyurethane cleaner aerosols to be connected directly to the application kit allowing the user to clear adhesive from the system in situ.

### Features and Benefits

- Prevent blockages before they occur
- Reduce down-time attributed to kit maintenance
- Enable longer term storage of kit between projects with no adhesive cure in storage.



### Guidelines for Use:

1. Always wear appropriate protective equipment prior to carrying out the cleaning procedure. It is the user's responsibility to ensure they have the appropriate protection
2. Ensure the valve on the canister is completely turned off prior to attaching the Flushing System. If the application kit has been in use, ensure that the system has been depressurised prior to removing the hose from the canister valve.
3. Attach the Flushing System to the valve. Ensure that the assembly remains vertical when tightening.
4. Attach the hose to the Flushing System. Ensure that the assembly remains vertical when tightening the hose.
5. Ensure that the tap on the Flushing System is off before attaching the cleaning aerosol.
6. Screw the cleaning aerosol into the adaptor. Turn the tap to the "on" position to release the cleaning aerosol into the hose.
7. Aim the MCUP application gun into a suitable waste container and apply pressure to the trigger to release the cleaning aerosol through the hose and gun.
8. Allow the cleaner to dissolve any remaining residue for a minimum period of 15 minutes and repeat procedure. Maintain pressure until the adhesive has been expelled and the hose and gun are cleaned. There should be no visible residue of adhesive in the cleaning solvent.

**Disclaimer:** Every care has been taken to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact Flex-R. to check whether there have been any changes to the information since publication of the literature.

## Set-Up and Maintenance Guide

1. Always wear appropriate protective equipment prior to carrying out the cleaning procedure. It is the user's responsibility to ensure they have the appropriate protection
2. Ensure the valve on the canister is completely turned off prior to attaching the Flushing System. If the application kit has been in use, ensure that the system has been depressurised prior to removing the hose from the canister valve.
3. Attach the Flushing System to the valve. Ensure that the assembly remains vertical when tightening. (Image 1)
4. Attach the hose to the Flushing System. Ensure that the assembly remains vertical when tightening the hose.
5. Ensure that the tap on the Flushing System is off before attaching the cleaning aerosol.
6. Screw the cleaning aerosol into the adaptor. Turn the tap to the "on" position to release the cleaning aerosol into the hose. (Image 3)
7. Aim the MCPU application gun into a suitable waste container and apply pressure to the trigger to release the cleaning aerosol through the hose and gun. Maintain pressure until the adhesive has been expelled and the hose and gun are cleaned. There should be no visible residue of adhesive in the cleaning solvent. (Image 4)
8. Wait 15 minutes for residue to dissolve and repeat step 7.

**Disclaimer:** Every care has been taken to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact Flex-R. to check whether



Image 1: Canister Flushing Kit



Image 2: Canister Flushing Kit attached



Image 3: Tap "on" position



Image 3: Tap "on" position



Image 4: Cleaning application kit