

WEATHERED MEMBRANE CLEANER

ClassicBond Weathered Membrane Cleaner is used to clean both new and old EPDM membrane.

It helps to loosen and remove dirt and other contaminants from the surface of the membranes and leaves a suitable surface for the subsequent application of primer. Weathered Membrane Cleaner should be used when preparing EPDM membranes for application of primer, adhesives, Secure Tape, Pre-Applied Seam Tape (PST) and other Pressure Sensitive Accessories.

FEATURES & BENEFITS

- Easily removes dirt and other contaminants from EPDM membranes
- Prepares EPDM membrane for application of primer, adhesives and tape
- Prepares aged or contaminated TPO membrane

COVERAGE RATES

Coverage rate depends on the age of the membrane and the amount of dirt/debris on the surface. Assume 10m² (one surface) per litre.

APPLICATION*

1. Remove as much loose material as possible from the membrane surface where the adhesive or pressure sensitive product will be applied by brushing or wiping the area with a dry rag. Extreme conditions of accumulated dirt may require detergent and water cleaning (rinse area thoroughly with CLEAN water and allow to dry).
2. Saturate a clean rag with Weathered Membrane Cleaner. **SCRUB** the area in a circular motion. Continue to clean the area, changing wipes frequently, until the surface is a consistent matte black colour with no streaking. Additional cleaning is required at factory seams (scrub parallel to the seam). Allow to dry.
3. Apply primer according to product instructions and/or roofing system specification.

Review current specifications and details for specific application requirements.

WEATHERED MEMBRANE CLEANER

PRECAUTIONS

1. Review the applicable Safety Data Sheet for complete safety information prior to use.
2. Weathered Membrane Cleaner is **EXTREMELY FLAMMABLE**. This product contains materials that are fire and explosion hazards when exposed to heat, flame or sparks. Store and use away from all sources of heat, flame or sparks. Do not smoke while applying. Do not use in a confined or unventilated area. Vapours are heavier than air and may travel along ground to a distant ignition source and flash back.
3. During application, efforts must be made to prevent fumes from entering the building via air ventilation ducts. Do not place open containers or mix adhesive near fresh-air intake units. When possible, shut down or seal off the closest units.
4. Avoid breathing vapours. Keep container closed when not in use. Use with adequate ventilation. If inhaled, remove to fresh air. If not breathing, perform artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.
5. If swallowed, **DO NOT INDUCE VOMITING**. Seek medical attention.
6. Avoid contact with eyes. Safety glasses or goggles are recommended. If splashed in eyes, immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention.
7. Avoid contact with skin. Wash hands thoroughly after handling. In case of contact with skin, thoroughly wash affected area with soap and water.

Note: Permeation-resistant gloves (that meet ANSI/ISEA 105-2005) are recommended to be worn when using this product to protect hands from irritating ingredients.

8. **KEEP OUT OF THE REACH OF CHILDREN.**

Before using this product please ensure that you have been supplied with and have read carefully the following information:

1. The product labels
2. ClassicBond Weathered Membrane Cleaner Safety Data Sheet

PROPERTIES AND CHARACTERISTICS

Colour: Green

Solids: 0%

Flash Point: 18°C

Boiling Point: 127°C

Packaging: 18.9 Litre or 1 Litre