



- 1. ClassicBond PRO Fleece Reinforced EPDM
- 2. ClassicBond Decking Adhesive
- 3. ClassicBond Bonding Adhesive
- 4. Suitable thermal insulation, thickness determined by U-value
- 5. Air & Vapour Control Layer (AVCL)
- 6. Structural decking
- 7. Water Cut Off Mastic
- 8. Clamping Ring
- 9. Leaf Grate
- 10. 110mm Outlet Body



Notes:
1. This detail was prepared to serve as a guideline representing typical detailing conditions and illustrate the correct application of ClassicBond PRO products only. It may be necessary to modify this detail in whole or part in accordance with specific project conditions, design or requirements.
2. Remove fleece from membrane with electric heat gun prior to point 3
3. Install a continuous bead of water cut off mastic around drain
4. Use cutting guide supplied with outlet



www.ClassicBond.co.uk

| | | |
|----------------------|--|--|
| Title | | |
| FABRICATED PIPE SEAL | | |
| Product | | |
| DP-D-2 | | |

| | | |
|-----|----------|------------------|
| B | 02.04.14 | Text updated |
| A | 17.10.12 | PRODUCTION Issue |
| Rev | Date | Comments |

| | | | | |
|-------------|---------|----------|---------|----------|
| Drawn | Checked | Approved | Scale | Date |
| MFO | DW | DW | 1: 4@A4 | 17.10.12 |
| Status | | | | |
| PRODUCTION | | | | |
| Drawing No: | | | | Rev: |
| DP/D/2 | | | | B |